



DITEC SOFT RESET

The internal door for maximum flexibility



DITEC SOFT RESET

The Ditec Soft Reset is a compact self-reinserting roll-up door with a fully flexible curtain and soft bottom edge. The door offers improved looks, excellent sealing and easy operation.

Improved working conditions

OPTIMIZED PROCESS FLOW

The Soft Reset is designed for fast installation and easy operation. The quick opening and closing cycles and the self-reinserting function of the curtain reduce the risk of downtime after a crash and make this door the perfect solution for a smooth and trouble-free process flow!

ENERGY SAVINGS

Opening speeds up to 2,3m/s and fast closing make sure the door does not stay open longer than necessary; this results in important energy savings.

SEALING

The zippers are running in tight side guides, providing excellent sealing. They minimize the passage of air and infiltration of dirt. Optional gaskets are available in order to enhance the insulation capacity of the door.

LOW NOISE

A silent operation is assured by the specially designed side guides, the continuous zippers and special washers that absorb vibration.



User friendly operation

Safety assured

PROTECTION OF PEOPLE & GOODS

Possible obstacles will immediately be detected as the Soft Reset comes with a well-tested and field proven combination of 2 safety devices. In the unlikely event of a crash, the fully flexible curtain and soft bottom are designed not to cause any harm.

USER-FRIENDLY OPERATION

The control unit with its 32 digit LCD display will be your valuable assistant to keep you informed about the operation of the door. It is easy to adjust settings and plan maintenance. An accessible manual release system allows you to open the door quickly in case of an emergency.



Soft bottom edge

Smart & nice design

CREATIVE DESIGN AND ENHANCED LOOKS

The frame of the Soft Reset has a streamlined and robust construction. The upper cover with its sloping top is good looking and easy to clean. The rounded PVC side covers are a handsome addition to finish of the overall design.

LOW MAINTENANCE

The soft start and stop make the opening and closing movements well controlled. They reduce stress on the motor and decrease energy consumption. The Soft Reset has few moving parts and requires little maintenance. In case of a bottom-edge crash, repair works will usually be avoided as the curtain will automatically reintroduce itself when going up.

SPACE SAVING

The footprint of the Soft Reset is very small thanks to the 2 narrow columns. The compact structure of the frame and the small headspace for the rolled-up curtain assure a maximum passage height and width.



Perfect alignment

© Entrematic Group AB – 2019

Entrematic offers a comprehensive range of products for industrial, commercial, institutional and residential applications, including sectional doors, loading dock equipment, high-performance doors, residential garage doors, pedestrian doors, gates and barriers, and automation and operators. Built on nearly 200 years of accumulated expertise, Entrematic aims to be the most dynamic, innovative company in the entrance automation industry, and the best partner for dealers and installers. Our well-known brands include Normstahl, Dynaco, Ditec, EM and Nergeco.

Entrematic, Amarr, Kelly, Serco, Normstahl, Dynaco, Ditec, EM and Nergeco, as words and logotypes, are examples of trademarks owned by Entrematic Group AB or companies within the Entrematic Group.

The Ditec products are protected by worldwide registered patents. As part of its policy of continuous product development, Entrematic Group NV reserves the right to change the characteristics of its products or components without prior notice.

Disclaimers:

For a correct use of our products, please refer to our manual. Everything that is mentioned in this brochure is only valid under the terms of use in the user manual and on condition that the door was properly installed and maintained and has not undergone abuse nor neglect.

Your Ditec dealer:

ENTREMATIC BELGIUM NV
Waverstraat 21
B-9310 Moorsel-Aalst (Belgium)
Tel. +32 53 72 98 98
Fax. +32 53 72 98 50
info.ditec.eu@entrematic.com
www.ditecdoor.com

Ditec
ENTREMATIC