



DITEC TRAFFIC C/CM

The external door for intense traffic

www.ditecdoor.com

DITEC **TRAFFIC C/CM**

The Ditec Traffic C is a robust fold-up door, ideal for external applications. The Traffic CM is suitable for larger dimensions.

Improved working conditions

OPTIMIZED PROCESS ELOW

The 400V motor, combined with counterweights, allows the door to open and close fast. With the INVERTERmotion, speed can be differentiated and increased up to 1.3 m/s.

ENERGY SAVINGS

The high operating speed avoids the doors remaining open longer than needed. Thus, the working environment remains stable and energy can be saved.

WIND RESISTANCE

Thanks to the reinforcement bars in the curtain, the Ditec Traffic C/CM withstands wind loads up to class 2. The fold-up principle makes sure doors can close even under heavy wind load.

Safety assured

PROTECTION OF PEOPLE & GOODS

The self-testing, sensible bottom edge and the photocells or a light curtain detect possible obstacles and reopen the door when needed.

EMERGENCY OPENING

In case of emergency, a red handle can be turned to release the counterweight and open the door.

Smart & nice design

ITALIAN LOOKS

A Ditec Traffic C/CM door has a nicely finished doorframe. On the Traffic C, fully transparent sections are available for maximum visibility.

LOW MAINTENANCE

The Ditec Traffic C/CM, with its most accessible operating system, requires little maintenance.

SPACE SAVING

The Ditec Traffic C/CM requires limited installation space. Its self-supporting frame and the absence of a side-motor allows for installation in a corridor or any other limited space.

© Entrematic Group AB - 2018

Entrematic offers a comprehensive range of products for industrial, commercial, institutional and residential applications, including sectional doors, loading dock equipment, high-performance doors, residential garage doors, pedestrian doors, gates and barriers, and automation and operators. Built on nearly 200 years of accur mulated expertise, Entrematic aims to be the most dynamic, innovative company in the anteness unteraction inductor and the bart percent doc doclare or exit percents. the entrance automation industry, and the best partner for dealers and installers. Our well-known brands include Normstahl, Dynaco, Ditec, EM and Nergeco

Entrematic, Amarr, Kelly, Serco, Normstahl, Dynaco, Ditec, EM and Nergeco, as words and logotypes, are examples of trademarks owned by Entrematic Group AB or companies within the Entrematic Group.

The Ditec products are protected by worldwide registered patents. As part of its The Direc products are protected by workdwide registered patents. As part of its policy of continuous product development. Entrematic Corup NV reserves the right to change the characteristics of its products or components without prior notice. Disclaimers: For a correct use of our products, please refer to our manual. Everything that is mentioned in this brochure is only valid under the terms of use in the user manual and on condition that the door was properly installed and maintained and has not indicate an ender the second se

and has not undergone abuse nor neglect.

Your Ditec dealer:

Horizontal reinforcement bars



Emergency opening



Modular sections

ENTREMATIC BELGIUM NV Waverstraat 21 B-9310 Moorsel-Aalst (Belgium) Tel. +32 53 72 98 98 Fax. +32 53 72 98 50 info.ditec.eu@entrematic.com www.ditecdoor.com

